



CAM CLEATS 27/38

CAM CLEATS

Seldén cam cleats are made of carbon fibre reinforced polyetherimide. This material is selected for its high resistance to friction heat. There is also an aluminium version of cam cleat 38 available. The cleats have a compact design in order to save space.



1



Cam Cleat 27/38 Composite
Cam Cleat 38 Aluminium

2



Top Guide 27/38

3



Fairlead 27/38

4



Riser 27/38

5



Wedge Kit 27/38

6



Nut Recess 27/38

7



Bull's Eye 27/38



Cam cleat with top guide.



8



Line Guide 27/38

9



Curved Base 27/38

10



2-P Eye

CAM CLEAT 27

Rope capacity 3-7 mm. Hole spacing c-c 27 mm.

	Art. No.	Weight (g)	Safe working load (kg)
1	433-101-01R	15	90
2	433-108-01R	3	-
3	433-110-01R	14	-
4	433-115R	9	-
5	433-116-01R	5	-
6	433-118R	3	-
7	433-119-01R	6	-
8	433-113-01R	4	-
9	319-844	1	-

CAM CLEAT 38

Rope capacity 4-12 mm. Hole spacing c-c 38 mm.

	Art. No.	Weight (g)	Safe working load (kg)
1	433-201-01R	32	120
1	433-301-01R	57	180
2	433-208-01R	9	-
3	433-210-01R	37	-
4	433-215R	21	-
5	433-216-01R	15	-
6	433-414R	5	-
7	433-219-01R	16	-
8	433-213-01R	11	-
9	319-823	3	-
10	508-019	14	-

