

Eye w/ Socket (54-)



Article No	Rod Size		Ø Pin		W mm	X mm	Y mm	Z mm	L mm	Break Load Kg	Weight Kg
	Dash	mm	Inch	mm							
54516040	-3	4.0	5/16"	8.1	16.0	7.0	9.0	14.5	46.0	2000	0.042
54380045	-4	4.4	3/8"	9.6	20.0	8.5	10.0	17.0	56.0	2650	0.056
54716045	-4	4.4	7/16"	11.2	24.0	10.0	13.0	19.0	53.0	2900	0.090
54716050	-6	5.0	7/16"	11.2	24.0	10.0	13.0	19.0	57.0	3450	0.099
54716057	-8	5.7	7/16"	11.2	24.0	10.0	13.0	18.0	57.0	4450	0.098
54120050	-6	5.0	1/2"	12.8	28.0	11.0	15.0	21.5	57.0	3450	0.140
54120057	-8	5.7	1/2"	12.8	28.0	11.0	15.0	21.5	57.0	4500	0.139
54120060	-9	6.0	1/2"	12.8	28.0	11.0	15.0	21.5	57.0	4650	0.138
54120064	-10	6.4	1/2"	12.8	28.0	11.0	15.0	21.5	57.0	5650	0.137
54580064	-10	6.4	5/8"	16.0	32.8	14.0	17.0	24.5	74.0	6950	0.220
54120071	-12	7.1	1/2"	12.8	28.0	11.0	15.0	21.5	57.0	6400	0.137
54580071	-12	7.1	5/8"	16.0	32.8	14.0	18.0	24.5	77.0	6950	0.237
54580075	-15	7.5	5/8"	16.0	32.8	14.0	18.0	24.5	76.0	7400	0.238
54580080	-16	8.0	5/8"	16.0	32.8	14.0	18.0	24.5	76.0	8200	0.236
54580084	-17	8.4	5/8"	16.0	32.8	14.0	18.0	24.5	76.0	9700	0.235
54340084	-17	8.4	3/4"	19.1	37.5	17.0	20.0	30.0	85.0	9700	0.404
54340095	-22	9.5	3/4"	19.1	37.5	17.0	20.0	30.0	85.0	12450	0.400
54780111	-30	11.1	7/8"	22.3	44.0	19.5	26.0	35.0	100.0	17000	0.607
54100127	-40	12.7	1"	25.6	49.5	22.0	27.5	39.5	108.0	21500	0.838
54118143	-48	14.3	1 1/8"	28.8	57.0	25.0	31.5	46.5	118.0	27250	1.253

Material: Acidproof Stainless Steel

For Socket outer diameter see Socket (50-) page 36, same Dash size