

Stud w/ Socket (53-)



Article No	Rod Size		Thread Inch	D mm	L1 mm	L2 mm	L3 mm	SW mm	Break Load Kg	Weight Kg
	Dash	mm								
53516040	-3	4.0	5/16"-24RH	2.5	83.5	55.0	4.5	6	2100	0.04
53380045	-4	4.4	3/8"-24	2.5	10.0	71.5	6.0	8	2750	0.07
53716050	-6	5.0	7/16"-20	3.3	113.0	76.0			3600	0.10
53716057	-8	5.7	7/16"-20	3.3	113.0	76.0			4650	0.10
53120057	-8	5.7	1/2"-20	4.0	120.0	80.0			4650	0.14
53716060	-9	6.0	7/16"-20RH	3.3	113.0	76.0			4750	0.10
53120060	-9	6.0	1/2"-20	4.0	120.0	80.0			4850	0.14
53120064	-10	6.4	1/2"-20	4.0	120.0	80.0			5850	0.14
53120071	-12	7.1	1/2"-20	4.0	120.0	80.0			6260	0.14
53580071	-12	7.1	5/8"-18	4.0	156.0	101.0			7250	0.28
53580075	-15	7.5	5/8"-18	4.0	156.0	101.0			7750	0.28
53580080	-16	8.0	5/8"-18	4.0	156.0	101.0			8550	0.280
53580084	-17	8.4	5/8"-18	4.0	156.0	101.0			9850	0.28
53340084	-17	8.4	3/4"-16	4.0	180.0	120.0			10150	0.47
53340095	-22	9.5	3/4"-16	4.0	180.0	120.0			12950	0.46
53780111	-30	11.1	7/8"-14	5.0	233.0	156.0			17700	0.79
53100127	-40	12.7	1"-12-RH	5.0	242.5	166.5	8.6	22	21280	1.26
53114143	-48	14.3	1 1/4"-12RH	5.0	258.5	175.0			28450	1.90
53114168	-60	16.8	1 1/4"-12	5.0	266.0	175.0			37200	2.12

Material: Acidproof Stainless Steel

- For Socket outer diameter see under Socket (50-) same Dash Size