



Assembly instructions:

- Remove the 3 top screws with a size 2.5 hex key and separate the base from the light unit.
- Drill the black grommet of the base and run the cable through the hole.
- Fix the base with two M3 screws (not included) on a horizontal surface.
- Cut the cable to the requested length, leaving 10 cm (3.94 inch.) above the grommet.
- Strip the the 2 or 4 cable wires and plug each wire in the connector underneath the light unit.
- Do not worry about the polarity.

Particular case: the tricolour + anchoring light has 2 lots of contact studs: 1 for the tricolour light and the other for the anchoring light. Take notice of the wire colours connected to each contact stud.

- To strengthen the water tightness, plaster the inside of the grommet's cavity with silicon mastic.
- Roll the cable up in the base unit, fix the light unit on by tightening gently the 3 top screws.
- Switch on and validate the functioning

Product compliant with the marin equipment directive 2014/90/EU

Electrical supply :

Not polarized
10-32 VDC, Max 4W

Mecanical :

Temperature -30°C ; + 70°C
Waterproof IP67, weight 250g.

End of life behavior :

The lifetime of the light is set at 45000 hours.
After this limit, the light will flash during 10 seconds when switched on. This indicates that the product needs to be replaced.

MANTAGUA

Title

Navipro

No. of plan

user instructions

A4