

# KBO Range

\*Block safe working load. The lashing may hold a higher load - X: not available

MODEL	REFERENCE	WORKING LOAD (Kg)	BREAKING LOAD* (Kg)	WEIGHT (g)	MAX. LINE DIAMETER (mm)	SHEAVE DIAMETER (mm)	CORRESPONDING ROPE SHACKLE REFERENCE	CORRESPONDING GUIDE REFERENCE
<b>KBO1</b>	PF830030	150	300	10	6	22,5	MP551865	X
<b>KBO1 double</b>	PF830030 - D	250	500	17,5	6	22,5	MP553117	X
<b>KBO1 triple</b>	PF830030 - T	350	700	25	6	22,5	MP553118	X
<b>KBO2</b>	PF790030	220	440	26	8	32	MP551701	X
<b>KBO2 double</b>	PF790030 - D	350	700	50	8	32	MP553119	X
<b>KBO2 triple</b>	PF790030 - T	450	900	72	8	32	MP553120	X
<b>KBO4</b>	PF650030	400	800	27	8	32	MP551701	X
<b>KBO4 double</b>	PF650030 - D	650	1300	66	8	32	MP553119	X
<b>KBO4 triple</b>	PF650030 - T	900	1800	84	8	32	MP553120	X
<b>KBO6</b>	PF800030	600	1200	46	10	38	MP551148	X
<b>KBO6 double</b>	PF800030 - D	950	1900	103	10	38	MP553121	X
<b>KBO6 triple</b>	PF800030 - T	1300	2600	148	10	38	MP553122	X
<b>KBO8</b>	PF890030	850	1700	80	12	47	MP551148	X
<b>KBO8 double</b>	PF890030 - D	1300	2600	148	12	47	MP553123	X
<b>KBO8 triple</b>	PF890030 - T	1800	3600	213	12	47	MP553124	X
<b>KBO10</b>	PF660030	1200	2400	83	12	52	MP551148	PL662127
<b>KBO15</b>	PF670030	1800	3600	138	14	63	MP551149	PL672254
<b>KBO20</b>	PF680030	2600	5200	186	14	74	MP551149	PL682261
<b>KBO30</b>	PF690030	3500	7000	334	16	97	MP551150	PL692262
<b>KBO50</b>	PF810030	5000	10000	610	18	123	X	X